

LONSEAL

INSTALLER CHECKLIST

INTERIOR SUBSTRATES:

- #755 Adhesive** (Field)
- #300 Epoxy Adhesive** (Extreme Use)
- Double-Face Tape** (Under Seams)
- Lonsealer Type A**

OR

- Welding Thread**
- Urethane Products** (i.e. TOPSEAL): Must use #65 Urethane Nozzle for heat welding

EXTERIOR SUBSTRATES:

- #200 Single-Ply Bonding Adhesive**
- #400 Contact Adhesive** (wrapping pipes, stairs and upholstered edges)
- #300 Epoxy Adhesive** (At exposed edges of deck, drains, pipes, etc.)
- GeoCel 2300** (use caulk at exposed edges)

MAINTENANCE PRODUCTS:

- Loncare** – neutral pH damp mop floor cleaner
- Lonbuff** – spray buff floor cleaner for glossy urethane surfaced products
- Lonprime** – floor sealer that increases adhesion of floor finish to Lonseal Flooring (eliminates peeling of floor finish)
- Lonfinish** – high performance glossy floor finish
- Lonsatin** – high performance matte floor finish
- Lonstrip** – no-rinse, highly effective floor finish stripper

Continued...

Trowel Specifications and Roller Spread Rate Table

#755	Interior Porous			Exterior Porous
	V-notch	U-notch	Nap Roller	Square notch
Trowel:	1/16" x 1/16" x 1/16"	1/32" x 1/16" x 1/32"	3/8"	1/16" x 1/16" x 1/16"
*Spread / gal.	170-210	185-245	180-200	160-180
**Minutes open time	15-30	15-30	15-30	15-30
**Minutes working time	60	60	60	60

*Actual job site coverage may vary according to substrate conditions
 **Average minutes at 70°F (21°C).

ADHESIVES & SUNDRIES:

- #755 Adhesive:** 3.5 gal. unit & 1 gal. unit (See Table Above)
- #400 Contact Adhesive:** 1 gal. unit (average coverage - 150 sq. ft./per surface)
Maintain application of adhesive to both surfaces (substrate + vinyl)
- #300 Epoxy Adhesive:** 1 gal. unit (average coverage - 110 sq. ft.)
(Extreme Use – i.e. Elevators & Bathrooms)
- #200 Single-Ply Bonding Adhesive:** 3.5 gal. and 1 gal. unit (average coverage - 140-180 sq. ft./gal/surface)
- Lonsealer Type A:** 1 Tube 4.5 oz (average coverage - 200 lin. ft.)
- Double-Face Tape:** 1 roll (coverage 2" x 60')
- Welding Thread:** 100 ft. min or 1 spool @500 ft.
- Loncare:** 1 gal. unit (average coverage - 2,000 sq. ft./gal)
- Lonbuff:** 1 gal. unit (average coverage - 4,500 sq. ft./gal)
- Lonprime:** 1 gal. unit (average coverage - 3,500 sq. ft./gal)
- Lonfinish:** 1 gal. unit (average coverage - 2,500 sq. ft./gal)
- Lonsatin:** 1 gal. unit (average coverage - 2,500 sq. ft./gal)
- Lonstrip:** 1 gal. unit (average coverage - 2,000 sq. ft./gal)
- GeoCel 2300** – Use caulk at exposed edges. 1 - 10.6 fl. oz. Cartridge
 Theoretical Yield per Cartridge:

Joint Size	Linear Feet
1/4" x 1/4"	25.5
1/4" x 3/8"	16.9
1/2" x 3/8"	8.4
1/2" x 1/2"	6.4
3/4" x 1/2"	4.2

LONGSEAL

WWW.LONSEAL.COM

Updated Oct. 7, 2011

Additional information can be obtained within the Technical Manual for Exterior Products.